



Once Applied on a Porous Surface, Improves the Yield of Final Coating and Saves Money

Prime Sealer®

Contains 25% of pure Nano Acryl GP

Ready to be applied - Any kind of dilution will void the warranty

Warranty	10 years
Yield per Liter	3.0 – 6.0 m ²
Elongation Capacity	more than 500%
Adhesion Strength	more than 350 tons x m ²
Contact Temperature	-25° C / +110° C

Prime Sealer is an acrylic primer for porous construction materials.

It's made from our green 100% acrylic, nano-pollution free nano-resin Nano Acryl GP.

Prime Sealer can be applied on any kind of porous materials, having an exceptional strength of adhesion and will last for 10 years or more.

It's washable with common household detergents and chlorine and is Anti-fungi, Anti-algae.

Prime Sealer seals any pore and does not permit penetration of water or moisture into protected construction material.

Prime Sealer resists :

Extreme Weather – Salinity and Humidity of Marine Environment
 Pollution - Animal Waste - Bird Drops - Permanent Puddles - Inorganic acids

All Nasacoat Coatings are 100% Acrylic - 100% Water Based
 Non toxic - 100% Ecological = Environmental Friendly and Sustainable
 as well as

100% Free of cheap monomers : Styrene, Vinyl and VEOVA
 100% free of poisoning : Ammonia, Lead, Heavy Metals, Organic Vapors Emission = 0 VOC

Sustainable Materials for a Better and Healthy Future



Once Applied on a Porous Surface, Improves the Yield of Final Coating and Saves Money

Prime Sealer®

Contains 25% of pure Nano Acryl GP

Ready to be applied - Any kind of dilution will void the warranty

Technical Characteristics

Yield per Liter (m ²)	3.0 – 6.0	Elongation Capacity	> 500%
Content of Nano Acryl GP	25%	Flexibility	180°
VOC	< 5 g / L - 0 VOC	Adhesion Strength	> 3.4 MPa
Density	1.09 g / ml	Adhesion Strength x m ²	> 350 Tons
Solids	17%	Temperature Resistance	- 25° / + 110°
Viscosity	950 – 1,300 cps	Touch Dry	1 hour.
pH	8.0 - 9.5	Total Drying	2 hours
Maximum Storing Time	12 months	Total Curing time	36 hours
Maximum Storage Temperature	35°	Warranty	10 years

Prime Sealer can be easily applied with common brushes, rollers or, as best solution, with airless machine. It does not need any dilution, it's ready to apply.

Prime Sealer is applied with 1 coat only. If applied on an extremely porous surface, like chalk, stucco, ancient wood, clay or similar, may require the application of a second coat.

See the Application Manual at : www.nasacoat.com/en/application_manual.pdf

Exclusive Distributor in Mexico :

Nasacoat de México SA de CV Av. López Mateos # 2077 - Plaza del Ángel - Local 9 - Nivel 1,
 Jardines de Plaza del Sol - 44510 Guadalajara, Jalisco - Mexico

Phone : +52 33 3696 10 51 email : team@nasacoat.com www.nasacoat.com